

REAR VISION CAMERA

MODEL: UEE-2201

2Ch 7" Digital LCD Monitor



1. HD 2 channels, 2 split H.246 Compression
2. SD memory storage support (Max. 128GB).
3. Resolution of monitor: 1,024 x 3(RGB) x 600 Pixels
4. PAL/NTSC switching
5. Video quality up to 1080P resolution
6. Supports 2channels or 4 channels video input.
7. Support 2video mode: manual, alarm, timing, trigger
8. Additional 2Ch inputs with triggers
9. Full CH, Auto Scan, Trigger CH & Live display
10. Support CVBS/960H/AHD camera
11. 2CH AV Inputs with 1080p/720P/960H/D1
12. Date & Time Stamp, vehicle information, channel number on the file
13. Playback a Recorded file on the LCD
14. Setup on the LCD menu
15. Built-in Circuit protection chip from over voltage & reversing voltage
16. Professional In-Vehicle power design, 6-36V DC Wide Voltage Range

BACK VIEW CAMERA

MODEL: AC-053IR

- Sony CCD Camera, 1.3 Megapixel, 2 megapixel (optional)
- Lens: 2.8mm
- Min illumination: 0 Lux (LED ON)
- IR led: 18pcs
- System: PAL/NTSC optional
- Pixel: 1280(H)*720(V).
- Night Vision distance: 45ft
- Waterproof: IP68
- View angle: 120°
- Power voltage: 12V-24V
- Operation Temp.: -20°C~+75°C
- Sunshade Design
- Connectors: 4pin Aviation
- Environmental test grade: IP69K as per DGMS circular.



CONNECTING CABLE

MODEL: SC-015

VIDEO EXTENSION CABLE:

1. 5MTR, 10MTR, 15MTR & 20Meters (OPTINAL) video and power cable
2. Female and Male extension cable
3. For bus and truck, lifting cranes, and all commercial vehicles.
4. Waterproof, Shock proof, Reliable connectivity compared to RCA/AV cables
5. Connectors: 4pin Aviation

